

F SERIES

# FORMA

EUROPEAN HERITAGE

# F Series

RELIABLE • DEPENDABLE • EFFICIENT



Connected Tractor



Projector Headlamps



LED Lights



Power Steering

FORMA



## F SERIES - SPECIFICATIONS

MODEL	F40	F45	F50
Operator Station	Non-cab		
Traction	2WD/MFWD		
ENGINE			
Model	A40	A45	A50
Type	TREM IIIA, Water Cooled, 4 Stroke, Naturally Aspirated, Direct Injection, Diesel Engine		
Displacement (cc)	2858	2858	3065
Engine HP*	40	45	49.5
Fuel System	Inline Fuel Injection Pump		
Fuel Capacity (l)	55		
Alternator (Amp)	42		
TRANSMISSION			
Standard	8 + 2		
Differential Lock	Available in 2WD as Optional	Available in 2WD as Optional	Optional in Both
MFWD Engagement	Mechanical Engagement		
3-POINT HITCH FEATURES			
3-Point Hitch Category	Cat II/I		
Draft Sensing or Lift Control	Top link sensing		
3-POINT HITCH LIFT Capacity			
Standard Lift Capacity at ballend	1200	1600	1800
AXLES			
Front	2WD or MFWD with Limited Slip		
PTO			
PTO Speed	540 RPM		
HYDRAULICS			
System Type	Open Center		
Number of Rear Remotes	2		
Hydraulic Pump Flow (lpm)	34	38	39
DIMENSIONS & WEIGHTS			
Wheelbase (2WD)	1960	1960	1968
Overall Length	3600	3660	3660
Overall Height (2WD)	2300	2300	2310
Tractor Weight without Ballast (2WD)	1930	1950	2010
BALLAST			
Front Weights (Optional)	22 kg x 4 Qty.		
TIRES			
Front (2WD)	6.00-16	6.00-16	7.50-16
Rear (2WD)	13.6x28	14.9x28	14.9x28
Front (MFWD)	8.00-18	8.00-18	8.3-24
Rear (MFWD)	13.6x28	13.6x28	14.9x28



Authorised Dealer :



**Mktg. H.Q. :** 4th Floor, Pinnacle, Surajkund  
NCR-121009, India

Ph. : +91-129-4550000

Email : [info@forma-international.com](mailto:info@forma-international.com)

Website : [www.forma-international.com](http://www.forma-international.com)

**Note :** In view of policy of continuous improvements, technical specifications can be varied without prior information. For detailed information please consult Team FORMA or Authorized Dealer Accessories shown are not part of the standard equipment specification may vary as per markets.