

FORMA

EUROPEAN HERITAGE

F Series

RELIABLE • DEPENDABLE • EFFICIENT



Connected Tractor



Projector Headlamps



LED Lights



Power Steering





F SERIES - SPECIFICATIONS



MODEL	F60	F75	F90
Operator Station	Non-cab		
Traction	2WD/MFWD		
ENGINE			
Model	A65	A75 TC	A90 TC
Type	TREM IIIA, Water Cooled, 4 Stroke, Naturally Aspirated, DI, Diesel Engine	TREM IIIA, Water Cooled, 4 Stroke, Turbocharged, DI, Diesel Engine	TREM IIIA, Water Cooled, 4 Stroke, Turbocharged with intercooler, DI, Diesel Engine
Displacement (cc)	4088		
Engine HP*	61.2	74.8	89.8
Fuel System	Inline Fuel Injection Pump		
Fuel Capacity (l)	65		
Alternator (Amp)	42		
TRANSMISSION			
Standard	8+2 / 12+12	12+12	
Differential Lock	Available		
MFWD Engagement	Mechanical Engagement		
3-POINT HITCH FEATURES			
3-Point Hitch Category	Cat II/I		
Draft Sensing or Lift Control	Top link sensing		
3-POINT HITCH LIFT Capacity			
Standard Lift Capacity at ballend	2000 / 2200 kg	2200 kg	2500 kg
AXLES			
Front	2WD/MFWD	MFWD	
PTO			
PTO Speed	540, 540E		
HYDRAULICS			
System Type	Open Center		
Number of Rear Remotes	4		
Hydraulic Pump Flow (lpm)	49.5		
DIMENSIONS & WEIGHTS			
Wheelbase (4WD)	2200 / 2235	2235	2265
Overall Length	3845 / 3990	3990	4020
Overall Height (4WD) with ROPS	2500 / 2600	2650	2670
Tractor Weight without Ballast (4WD)	2515 / 2785	2841	2976
BALLAST			
Front Weights (Optional)	22 kg x 4 Qty.		
TIRES			
Front (2WD)	7.50-16	—	—
Rear (2WD)	16.9x28	—	—
Front (MFWD)	9.5x24	11.2x24	12.4x24
Rear (MFWD)	16.9x28	16.9x30	18.4x30



Authorised Dealer :



Mktg. H.Q. : 4th Floor, Pinnacle, Surajkund
NCR-121009, India

Ph. : +91-129-4550000

Email : info@forma-international.com

Website : www.forma-international.com

Note : In view of policy of continuous improvements, technical specifications can be varied without prior information. For detailed information please consult Team FORMA or Authorized Dealer Accessories shown are not part of the standard equipment specification may vary as per markets.